

ATM Interface Transformers

Designed for 155Mbps ATM applications over UTP-5 cable

Supports 100 Base-X and Twisted Pair FDDI

Supports either transmit or receive channels

IEEE 802.3 Compatible

Low common mode emissions


Fast Rise Times

Electrical Specifications at 25° C

PARAMETER	TYP.	UNITS
Insertion Loss (0.1 to 125 MHz)	-1.1	dB
Rise Time (10 to 90%)	4.0	ns
Return Loss: (0.1 to 60 MHz) TX (0.1 to 60 MHz) RX (60 to 100 MHz) TX (60 to 100 MHz) RX	-15 -17 -11 -14	dB dB dB dB
Differential to Common Mode Rejection (0.1 to 60 MHz) TX (0.1 to 60 MHz) RX (60 to 100 MHz) TX (60 to 100 MHz) RX	-42 -40 -40 -35	dB dB dB dB
Crosstalk (0.1 to 60 MHz) (60 to 100 MHz)	-40 -38	dB dB
Isolation Min.	1500	Vrms


TX = TRANSMIT CHANNEL
RX = RECEIVE CHANNEL

SCHEMATICS



URNS RATIOS 1CT : 1CT (TX) / 1CT : 1CT (RX)

Dimensions in Inches (mm)



Available on
Tape & Reel

Rhombus P/N: **T-15506**

Cust. P/N:

Name:

Date: **4/22/99**

Sheet: 1 of 1